

Podkładka podatna stożkowa / Conical spring washers for bolted connections


Norma
Standart

DIN 6796
ISO 10670

Zakres / Range M 5 ÷ M 30

Kl. wł. mech. / Property class

Materiał / Material Stal, Stal nierdzewna
Steel, stainless steel



d_{nom}	5	6	8	10	12	14	16
Pod gwint Thread dia.	M 5	M 6	M 8	M 10	M 12	M 14	M 16
d_1	5,3	6,4	8,4	10,5	13	15	17
d_2	11	14	18	23	29	35	39
h	min	1,35	1,7	2,24	2,8	3,43	4,04
	max	1,55	2	2,6	3,2	3,95	4,65
s_{nom}	1,2	1,5	2	2,5	3	3,5	4

d_{nom}	18	20	22	24	27	30
Pod gwint Thread dia.	M 18	M 20	M 22	M 24	M 27	M 30
d_1	19	24	23	25	28	31
d_2	42	45	49	56	60	70
h	min	5,08	5,6	6,15	6,77	7,3
	max	5,8	6,4	7,05	7,75	8,35
s_{nom}	4,5	5	5,5	6	6,5	7

Przykład oznaczania podkładki okrągłej podatnej stożkowej o wielkości nominalnej 8

Podkładka DIN 6796 - 8 Fst

Example designation conical spring washer bolted connections, nominal size 8

Washer DIN 6796 - 8 Fst

1/1

